



L12-KARAMOOTTORI

Pieni karamoottori

L12-100-100-6-S
Karamoottori



- 6/12 VDC
- 80N
- 20% käyttöaste
- IP54
- Isku 10-100mm

TUOTEKUVAUS

Actuonix Motion Devices valmistaa kompakteja ja pieniä karamoottoreita.


L12 sarja on monipuolinen perusominaisuuksiltaan ja lisävarusteena on saatavana potentiometri ja päätyrajakytkimet.

TEKNISEET TIEDOT

IP-luokka	IP54
Iskun pituus	100 mm
Käyttöjännite	6,0 V DC
Käyttösykli	20 %
Max. käyttölämpötila	50 °C
Max. työntövoima	42 N
Max. vetovoima	42 N
Min. käyttölämpötila	-10 °C
Nimellisa nopeus, ei kuormaa	13 mm/s
Paino	56 g
Pitovoima	22 N
Välityssuhde	100:1
Äänenpaine	55 dB

feature

<i>feature</i>	<i>Options</i>
SS: Stroke Length	10, 30, 50, 100
GG: Gear reduction ratio (refer to load curves above)	50, 100, 210 (lower ratios are faster but push less force, and vice versa)
VV: Voltage	6, 12 (DC volts)
C: Controller	S Limit Switches P Potentiometer Feedback I Integrated Controller R RC Servo Integrated Controller



feature

<i>feature</i>	<i>Options</i>
SS: Stroke Length	10, 30, 50, 100
GG: Gear reduction ratio (refer to load curves above)	50, 100, 210 (lower ratios are faster but push less force, and vice versa)
VV: Voltage	6, 12 (DC volts)
C: Controller	S Limit Switches P Potentiometer Feedback I Integrated Controller R RC Servo Integrated Controller

