

PQ12-KARAMOOTTORI

Kompaktein malli

PQ12-63-12-P

Karamoottori

- 6/12 VDC
- 40N
- 20% käyttöaste
- 20mm isku
- IP54



TUOTEKUVAUS

PQ12 on kompaktein malli Actuonixin karamoottoreista. Se painaa vain 15 grammaa.

Tämä malli onkin erittäin sopiva kohteisiin, jossa tarvitaan tarkkaa liikettä, mutta asennustilaa ei ole paljon.


Tästä mallista on saatavilla kolme eri versiota:

- PQ12-P paikkatietoa-anturilla
- PQ12-S rajakytkimillä
- PQ12-R lineaariservo

TEKNISET TIEDOT

IP-luokka	IP54
Iskun pituus	20 mm
Jännite DC	12 V
Käyttösykli	20 %
Max power	45 N
Max. käyttölämpötila	50 °C
Min. käyttölämpötila	-10 °C
Nimellisa nopeus, ei kuormaa	15 mm/s
Pitovoima	25 N
Välityssuhde	63:1
Äänenpaine	55 dB

feature	options
GG: Gear reduction ratio (refer to load curves above)	30, 63, 100 (lower ratios are faster but push less force, and vice versa)
VV: Voltage	6, 12 (DC volts)
C: Controller	P Potentiometer Feedback S Limit Switches R RC Linear Servo (6V Only)



feature	options
GG: Gear reduction ratio (refer to load curves above)	30, 63, 100 (lower ratios are faster but push less force, and vice versa)
VV: Voltage	6, 12 (DC volts)
C: Controller	P Potentiometer Feedback S Limit Switches R RC Linear Servo (6V Only)

