

AKSIAALIVALO

DL225-sarja

SERIE-DL225

DL225 aksiaalivalo



- Valaisu kameran kuvaussuunnasta
- Useissa eri aallonpituuksissa
- Saatavana 25mm - 150mm kokoisena

TUOTEKUVAUS

DL225 nelikulmainen aksiaalivalo on toteutettu modulaarisella rakenteella joka mahdollistaa useiden eri kokojen toimittamisen nopeasti. Valot ovat saatavissa useissa eri aallonpituuksissa ultraviolettista infrapunaan. Pienin DL225-025 tarjoaa noin 18kLux ja suuremmat valot noin 50 kLux intensiteetin.

Konenäkövalaisimista löytyy monia eri vaihtoehtoja. Voit myös tutustua oheiseen valmistajan [valintatyökaluun](#) tai ottaa yhteyttä OEM asiakaspalveluun ja tuotealuepäällikköön.

DL225-025

Model	Lighted Length	Spectral Wavelength	Connector/Control	Alternative Connector
DL225	XXX	XXX	XX	XXX
DL225	025	(UV) 365 ² (UV) 375 ² (UV) 385 ² (UV) 395 ² (UV) 405 ² (deep blue) 455 (blue) 470 (green) 530 (amber) 590 (red) 625 (IR) 850 ² (IR) 940 ² (white) WHI	C1 C5 IC I3 I3S 24	M12 ¹

Ex: DL225-025470C1
DL225-025WHIIC-M12

¹ Available with IC, I3, I3S and 24v options only

² Not available in 24v option

DL225-050

Model	Lighted Length	Spectral Wavelength	Connector/Control	Alternative Connector
DL225	XXX	XXX	XX	XXX
DL225	050	(UV) 365 (UV) 375 (UV) 385 (UV) 395 (UV) 405 (deep blue) 455 (blue) 470 (green) 530 (amber) 590 (red) 625 (IR) 850 (IR) 940 (white) WHI	C1 C5 IC I3 I3S 24v	M12 ¹

Ex: DL225-050470C1
DL225-050WHIIC-M12

¹ Available with IC, I3, I3S and 24v options only

DL225-075

Model	—	Lighted Length	Spectral Wavelength	Connector/ Control	—	Alternative Connector
DL225	—	XXX	XXX	XX	—	XXX
DL225		075	(UV) 365 ² (UV) 375 ² (UV) 385 ² (UV) 395 ² (UV) 405 ² (deep blue) 455 (blue) 470 (green) 530 (amber) 590 (red) 625 (IR) 850 (IR) 940 ² (white) WHI	C1 C5 IC I3 I3S 24		M12 ¹
Ex: DL225-075470C1 DL225-075WHIIC-M12		¹ Available with IC, I3, I3S and 24v options only ² Not available in 24v option				

DL225-100

Model	—	Lighted Length	Spectral Wavelength	Connector/ Control	—	Alternative Connector
DL225	—	XXX	XXX	XX	—	XXX
DL225		100	(UV) 365 (UV) 375 (UV) 385 (UV) 395 (UV) 405 (deep blue) 455 (blue) 470 (green) 530 (amber) 590 (red) 625 (IR) 850 (IR) 940 (white) WHI	C1 C5 IC I3 I3S 24		M12 ¹
Ex: DL225-100470C1 DL225-100WHIIC-M12		¹ Available with IC, I3, I3S and 24v options only				

DL225-150

Model	—	Lighted Length	Spectral Wavelength	Connector/ Control	—	Alternative Connector
DL225	—	XXX	XXX	XX	—	XXX
DL225		150	(UV) 365 (UV) 375 (UV) 385 (UV) 395 (UV) 405 (deep blue) 455 (blue) 470 (green) 530 (amber) 590 (red) 625 (IR) 850 (IR) 940 (white) WHI	C1 C5 IC I3 I3S 24		M12 ¹
Ex: DL225-150470C1 DL225-150WHIIC-M12		¹ Available with IC, I3, I3S and 24v options only				

TEKNISET TIEDOT

Aallonpituus	WHI, 365, 375, 385, 395, 405, 455, 530, 590, 625, 850, 940
Elinikä	50000 h
Hyväksynät	CE, RoHS
IP-luokka	IP50
Kaapelin pituus vakiona	2m
Liitäntä	C1, C5, IC, I3, I3S, 24
Max. käyttölämpötila	60 °C

Min. käyttölämpötila

0 °C
