

KOMPAKTI LÄMPÖTILALÄHETIN

TFT35

TFT35-14291009

DIN-A 0-10V 3-wire -50-150°C 75x6mm G1/2"

- Mittausalue -50-200 °C
- 4-20mA, 0-10V tai 0,5-4,5V ulostuloilla
- Asennuspituus 25-500mm
- DIN-A tai M12x1 sähköliitännällä



TUOTEKUVAUS

Lähetin soveltuu kohteisiin, joissa paine on alle 40 bar ja sen sähköiset osat on suojattu roiskevedeltä ja sillä on hyvä tärinän kesto. Yhdistetty suojatasku ja kierreltiitos tai säädettävä paineliitos mahdollistavat instrumentin asentamisen suoraan prosessiin.

TEKNISEET TIEDOT

Aineen kanssa kosketuksissa olevien osien materiaali	Ruostumaton teräs
Asennussyvyys	75 mm
IP-luokka	IP65
Liitântäkierre	G1/2"
Max. aineen lämpötila	150 °C
Max. painealue	50 bar
Max. syöttöjännite DC	30 V DC
Max. ympäristön lämpötila	85 °C
Min. aineen lämpötila	-50 °C
Min. syöttöjännite DC	10 V DC
Min. ympäristön lämpötila	-40 °C
Pistokkeen halkaisija	6 mm
Rungon materiaali	Ruostumaton teräs

Technical drawings illustrating various connector types and their dimensions:

- Angular connector DN EN 17531-803:** Shows a side view with dimensions 15, 18, and $\varnothing 72$. A detail view shows a cross-section with $\varnothing 1$.
- Circular connector M12 x 1:** Shows a side view with dimension 15.
- With neck tube:** Shows a side view with dimensions 15 and 18.
- With compression fitting:** Shows a side view with dimensions 15 and 18.
- Without process connection:** Shows a side view with dimension 15.

- Circular connector M12 x 1

- Circular connector M12 x 1

The image displays five technical drawings of angular correctors, arranged horizontally. Each drawing shows a side view and a cross-sectional view of the device, which is used to correct angular misalignment in piping. The drawings are labeled as follows:

- Angular corrector DIN EN 175301-603:** This drawing shows a device with a flange on one end and a threaded connection on the other. Dimensions include a total length of 150, a flange diameter of $\varnothing 72$, and a mounting hole diameter of $\varnothing 11$.
- Circular corrector M12 x 1:** This drawing shows a simpler, cylindrical device with a threaded connection. The length is dimensioned as 150.
- With neck tube:** This drawing shows a device with a flange and a neck tube. The total length is dimensioned as 150.
- With compression fitting:** This drawing shows a device with a flange and a compression fitting. The total length is dimensioned as 150.
- Without process connection:** This drawing shows a device with a flange and a process connection. The total length is dimensioned as 150.