

KAPILLAARILÄMPÖTILAMITTARI, STANDARDI MALLI

Perusmalli

IFC-14349096

Ø60, 0-120°C, L=5m, Sileä 150x8mm

- Mittausalue -100-400°C
- Näytön halkaisija 63, 80, 100, 72x72 eller 96x96
- Kotelo muovia paneeliasennusta varten
- Kapillaari jopa 5m
- Kapillaari muovia, kuparia tai ruostumatonta terästä



TUOTEKUVAUS

TEKNISET TIEDOT


Aineen kanssa kosketuksissa olevien osien materiaali	Messinki
Asennussyvyys	150 mm
Halkaisija	60 mm
IP-luokka	IP54
Kapillaarin materiaali	Kupari muovinen kansi
Kapillaariputken pituus	5000 mm
Lasin materiaali	Instrumenttilasi
Max. kaapelin lämpötilaresistanssi	120 °C
Max. käyttölämpötila	120 °C
Max. ympäristön lämpötila	70 °C
Min. kaapelin lämpötilaresistanssi	-40 °C
Min. käyttölämpötila	0 °C
Min. ympäristön lämpötila	-20 °C
Pistokkeen halkaisija	8 mm
Rungon materiaali	Muovi

NS 60



Plain stem (without thread), SF94
Copper alloy

Plain stem (without thread), SF94
Copper alloy
Insertion length = variable
Stem diameter $O_d = 6, 8, 8.5, 10$ mm



SF91/SV19 M14 x 1.5, R 1/2, R 1/2, R 1/2
Copper alloy
Insertion length = variable
Stem diameter $O_d = 6, 8, 8.5, 10$ mm




NS 60



Plain stem (without thread), SF94

Plain stem (without thread), SF94
Copper alloy
Insertion length = variable
Stem diameter $O_d = 6, 8, 8.5, 10$ mm



SF91/SV19 M14 x 1.5, R 1/4, R 1/4, R 1/4
Copper alloy
Insertion length = variable
Stem diameter $O_d = 6, 8, 8.5, 10$ mm

