

KAPILLAARILÄMPÖTILAMITTARI, STANDARDI MALLI

Perusmalli

IFC-14349097

Ø60, 0-120°C, L=2m, Sileä 150x8mm

- Mittausalue -100-400°C
- Näytön halkaisija 63, 80, 100, 72x72 eller 96x96
- Kotelo muovia paneeliasennusta varten
- Kapillaari jopa 5m
- Kapillaari muovia, kuparia tai ruostumatonta terästä






TUOTEKUVAUS



TEKNISET TIEDOT

Aineen kanssa kosketuksissa olevien osien materiaali	Messinki
Asennussyvyys	150 mm
Halkaisija	60 mm
IP-luokka	IP54
Kapillaarin materiaali	Kupari muovinen kansi
Kapillaariputken pituus	2000 mm
Lasin materiaali	Instrumenttilasi
Max. kaapelin lämpötilaresistanssi	120 °C
Max. käyttölämpötila	120 °C
Max. ympäristön lämpötila	70 °C
Min. kaapelin lämpötilaresistanssi	-40 °C
Min. käyttölämpötila	0 °C
Min. ympäristön lämpötila	-20 °C
Pistokkeen halkaisija	8 mm
Rungon materiaali	Muovi


Standard version






Standard version
Plain stem (without thread), SF94
 Copper alloy
 Insertion length = variable
 Stem diameter Ød = 6, 8, 8.5, 10 mm





Rotatable connection with loose threaded connection
SF91/SV19 M14 x 1.5, R 1/4, R 1/2, R 3/4
 Copper alloy
 Insertion length = variable
 Stem diameter Ød = 6, 8, 8.5, 10 mm



Standard version



Standard version
Plain stem (without thread), SF94
 Copper alloy
 Insertion length = variable
 Stem diameter Ød = 6, 8, 8.5, 10 mm



Rotatable connection with loose threaded connection
SF91/SV19 M14 x 1.5, R 1/4, R 1/2, R 3/4
 Copper alloy
 Insertion length = variable
 Stem diameter Ød = 6, 8, 8.5, 10 mm

