

PUTKITERMOELEMENTIN KOKOONPANOSARJA V-PAD

TC59-V

TC59-V
 Putkitermoelementin kokoonpanosarja V-PAD

- Mittausalue 0-1260°C
- Tyyppi K, J, N tai E
- Kestää erittäin suuria mekaanisia kuormituksia
- Materiaalina esimerkiksi Ruostumaton teräs ja Hastelloy
- ATEX optio



TUOTEKUVAUS

TEKNISET TIEDOT

Aineen kanssa kosketuksissa olevien osien materiaali

Hastelloy, Ruostumaton teräs


Max. käyttölämpötila

1260 °C

Min. käyttölämpötila


0 °C

Fixed connection (compression fitting) to the furnace




- Cable length 150 mm, other lengths on request
- Compensating cable type depending on the sensor type, PTFE-insulated
- The sealing from the process is performed by the compression fitting. It can be supplied in most common thread sizes.
- A connection head can be mounted directly to the neck or remotely.

Sliding connection (piston/spring) to the furnace



Fixed connection (compression fitting) to the furnace



- Cable length 150 mm, other lengths on request
- Compensating cable type depending on the sensor type, PTFE-insulated
- The sealing from the process is performed by the compression fitting. It can be supplied in most common thread sizes.
- A connection head can be mounted directly to the neck or remotely.

Sliding connection (piston/spring) to the furnace

