

JALKAKYTKIN

Teollisuuskäyttöön

606.2220.015

Jalkakytin F2-U2Z/U2Z, 2-poljin, 2 NO+2 NC,
hidaskosketin

- Tukeva rakenne
- Kotelointiluokka IP65
- Rele, kontaktori ym. voidaan asentaa suojan sisään
- Saatavana myös erikoismalleja esim. sairaalakäyttöön



TUOTEKUVAUS

Koodien selitykset:

F1 = 1 poljin

F2 = 2 poljinta

UN = Varvassuoja

U1Z = Hidaskosketin, 1 NO+1 NC

U2Z =	Hidaskosketin, 2 NO+2 NC
SU1Z =	Momenttikosketin, 1 NO+1 NC (kosketin vaihtaa tilaansa vakionopeudella, "nakshtava")
SU2Z =	Momenttikosketin, 2 NO+2 NC (kosketin vaihtaa tilaansa vakionopeudella, "nakshtava")
U1Y =	"Push-push" –kosketin. Kerran painettaessa koskettimet vaihtavat tilaansa, ja toisen kerran painettaessa palautuvat alkutilaansa, 1 NO+1 NC.
U2ZD =	Kaksoistoiminta: ensimmäinen kosketinpari toimii painettaessa poljinta vasteeseen asti, toinen pari kytkeytyy mukaan kun poljinvoimaa lisätään ja painetaan pohjaan asti, 2 NO+2 NC.

TEKNISET TIEDOT

TIEDOT

Koskettimet	2 NO, 2 NC
IP-luokka	IP65
Max. jännite	240 V
Nimellisvirta, terminen	10 A
Kaapelisisäänmeno	1xM20x1,5
Rungon materiaali	Alumiini
Polkimen määrä	2
Polkimen materiaali	Muovi
Min. käyttölämpötila	-30 °C
Max. käyttölämpötila	80 °C
Max. toimintataajuus	50 kertaa/min
B10d	20x10^6
Hyväksynnät	CCC, CE, CSA US

Standard values for safety technology

EN60947-1:2018
6 x 10⁶ Restrictions in article designation "C"
6 x 10⁶ Restrictions in article designation "D"
6 x 10⁶ Restrictions in article designation "E"
6 x 10⁶ Restrictions in article designation "F"

* Once a restriction exists, the lowest value needs to be applied.

This technical data is generic to our standard foot switch range; please refer to individual technical data sheets for exact product information as the technical data above may vary.

Standards

IEC 60947-1:2018, DIN EN 60947-1, IEC 60947-1
IEC 60947-2:2018, DIN EN 60947-2, IEC 60947-2

Approvals*

CE, ATEX, Q900 (same policy)
UL, ENEC (in type designation "D")
DIN EN 60947-1:2018 (in type designation "D")

* Approvals depend on type.
More information can be found in the data sheet.

Mechanical data

Enclosure Cast aluminium (powder coated)
Cover, Protective shield DIN Cast aluminium (powder coated)
Foot pedal Thermoplastic
Operating temperature (with no icing / no condensation) -30°C to +80°C (-20°C to +40°C in type designation "D")
Storage temperature -30°C to +80°C (-20°C to +40°C in type designation "D")
Mechanical service life > 1 x 10⁶ switching cycles when using switches with potentiometer 1 x 10⁶
Switching frequency 10 min⁻¹ when using switches with potentiometer (20 min⁻¹)
Type of connection Screw connections (M3.5)
Conductor cross sections Single wire 0.3 – 1.5 mm² or stranded wire with female 0.3 – 1.5 mm²
Cable entry M20 x 1.5
Weight with cover 01 = 0.6 kg, 02 = 1.7 kg, 03 = 3.0 kg
Weight with protective shield DIN 01 = 1.5 kg, 02 = 3.6 kg, 03 = 5.4 kg
Protection class Protection class depends on type. Standard is IP 65.

Technical drawing of the foot switch showing dimensions: 190mm width, 220mm height, 65mm base width, 118mm mounting hole distance, and 57mm side width.

 11 — 12
 23 — 24

 31 — 32
 43 — 44

This technical data is generic to our standard foot switch range, please refer to individual technical data sheets for exact product information as the technical data above may vary.

More information can be found in the data sheet.

Enclosure	Cast aluminium (powder-coated)
Cover, Protective shroud UN	Cast aluminium (powder-coated)
Fast-rod	Thermoplastic
Operating temperature (with no icing / no condensation)	-30°C to +80°C, -20°C to +65°C in type designation "TX"
Storage temperature	-30°C to +80°C, -20°C to +65°C in type designation "TX"
Mechanical service life	> 10 years (without cycles when using switches with potentiometer 1 x 10 ⁶)
Switching frequency	30 min ⁻¹ when using switches with potentiometer 20 min ⁻¹
Type of connection	Screen connections (M8x5)
Conductor cross sections	Single wire 0.3 - 1.5 mm ² or stranded wire with strands 0.3 - 1.5 mm ²
Cable entry	M20 x 1.5
Weight with cover	F1 = 0.8 kg F2 = 1.7 kg F3 = 3.0 kg
Weight with protective shroud UN	F1 = 1.3 kg F2 = 2.6 kg F3 = 5.3 kg
Protection class	Protection class depends on type. Standard is IP 65.