

JALKAKYTKIN

Teollisuuskäyttöön

606.2330.021

Jalkakytin F2-SU1Z/SU1Z, 2-poljin, 1 NO+1 NC,
momenttikosketin

- Tukeva rakenne
- Kotelointiluokka IP65
- Rele, kontaktori ym. voidaan asentaa suojan sisään
- Saatavana myös erikoismalleja esim. sairaalakäyttöön



TUOTEKUVAUS

Koodien selitykset:

F1 = 1 poljin

F2 = 2 poljinta

UN = Varvassuoja

U1Z = Hidaskosketin, 1 NO+1 NC

Mechanical data	
Enclosure	Cast aluminium (powder-coated)
Cover, Protective shield UN	Cast aluminium (powder-coated)
Foot pedal	Thermoplastic
Operating temperature (with no icing / no condensation)	-30°C to +80°C (-20°C to +185°C in type designation "XT")
Storage temperature	-30°C to +80°C (-20°C to +185°C in type designation "XT")
Mechanical service life	> 1x 10 ⁷ switching cycles when using switches with potentiometer 3 x 10 ⁶
Switching frequency	30 min ⁻¹ when using switches with potentiometer 20 min ⁻¹
Type of connection	Socket connection (MS-5)
Conductor cross sections	Single wire 0.5 - 1.5 mm ² or stranded wire with ferrule 0.5 - 1.5 mm ²
Cable entry	M20 x 1.5
Weight with cover	F1 = 0.8 kg, F2 = 1.7 kg, F3 = 3.0 kg
Weight with protective shield UN	F1 = 1.5 kg, F2 = 2.8 kg, F3 = 5.4 kg
Protection class	Protection class depends on type. Standard is IP 65.