



Example for selecting a part number:

PART NO.	BODY MATERIAL	MATERIALS CONTACTING LINE MEDIA	OUTLET PRESSURE	SOFT GOODS MATERIAL		BACK UP RING	INLET AND OUTLET PORT TYPE	VENT PORT	INLET AND OUTLET PORT SIZE	FILTER OPTION	MAIN VALVE AND SEAT MATERIAL
				DYNAMIC	STATIC						
44-15	1	4	D	2	5	8	2	7			
44-15	1 - Brass	Brass, Nickel Alloy, 300 Series Stainless Steel	Spring load only 2-10-2000psi 0.7-14 bar 4-10-6000psi 0.7-28 bar	D - Nitrile, Buna-N, FKM, Viton (FKM), V-TINEL, PTFE, Polysulfone	Nitrile, Buna-N, FKM, Viton (FKM), V-TINEL, PTFE, Polysulfone	PTFE	1 - NPTF 2 - NPTF 3 - 1/2" NPTF	1/2" NPTF 1/2" NPTF 1/2" NPTF	6 - 1/2" 8 - 1/2" 3 - NO	2 - WITH Filter 3 - NO Filter 8 - PEEK	2 - Polysulfone (Inconel SP7) 8 - PEEK
6 - 316	316 Stainless Steel	Nickel Alloy, 300 Series Stainless Steel	Al and Other load only 0.7-41 bar	PTFE, PTFE, PTFE, PTFE	PTFE, PTFE, PTFE, PTFE	PTFE	1 - NPTF 2 - NPTF 3 - 1/2" NPTF	1/2" NPTF 1/2" NPTF 1/2" NPTF	6 - 1/2" 8 - 1/2" 3 - NO	2 - WITH Filter 3 - NO Filter 8 - PEEK	2 - Polysulfone (Inconel SP7) 8 - PEEK

*Filter not recommended for liquid service

2
GAUGE PORT OPTIONS 1/4" NPTF

- 0 - None
- 1 - One Gauge Port at 90°
- 2 - Two Gauge Port at 90°
- 3 - Two Gauge Port at 60° (left hand inlet)
- 4 - Outlet Port at 90° (left hand inlet)

