

LABO-F-SARJAN PAINEENSÄÄDIN

Laboratoriokäyttöön

LABO-F
 LABO-F-sarja

- Max. sisääntulopaine: 200 bar
- Max. ulostulopaine: 20 bar
- Ei-syövyttävät kaasut puhtauteen 5,0 asti (99,999 tilavuus-%)
- Paino: 2,6 kg



LABO-F




DOPPELREGULUS

TUOTEKUVAUS


Example for selecting a part number:

D43150	12	05	2
BASIC SERIES	GAS	OUTLET PORT CONNECTION	CONTROLLED PRESSURE RANGE
D43150 Labo-F	02 - Nitrogen 08 - Air 09 - Synthetic air 12 - Oxygen 13 - Nitrogen oxide 15 - CO ₂ and inert gases 16 - Flammable gases 17 - Calibration gases	00 - Without connection (3/8" female) 05 - Compression fitting 6 mm with hose nipple 6 mm separately	1 - 27 psig / 1.5 bar 2 - 34 psig / 2 bar 3 - 34 psig / 2 bar 4 - 20 psig / 1.5 bar
*Note: Other outlet connections are available			

D50711	12	0050	05
BASIC SERIES	GAS	CONTROLLED PRESSURE RANGE	OUTLET PORT CONNECTION
D50711 Doppelregulus	02 - Nitrogen 08 - Air 09 - Synthetic air 12 - Oxygen 13 - Nitrogen oxide 15 - CO ₂ and inert gases 16 - Flammable gases (except Propane and Acetylene) 17 - Calibration gases 42 - Compressed air (370 psig / 300 bar)	0050 - 0.27 psig / 0.02 bar 0100 - 1.45 psig / 0.10 bar 0500 - 7.25 psig / 0.50 bar 1000 - 14.5 psig / 1.00 bar 1500 - 27 psig / 1.5 bar	05 - Compression fitting 6 mm with hose nipple 6 mm separately
*Note: Other outlet connections are available			




All dimensions are reference & nominal
 Metric [indicated] equivalents are in brackets



Example for selecting a part number:

D43150	12	05	2
BASIC SERIES	GAS	OUTLET PORT CONNECTION	CONTROLLED PRESSURE RANGE
D43150 Labo-F	02 - Nitrogen 08 - Air 09 - Synthetic air 12 - Oxygen 13 - Nitrogen oxide 15 - CO ₂ and inert gases 16 - Flammable gases 17 - Calibration gases	00 - Without connection (3/8" female) 05 - Compression fitting 6 mm with hose nipple 6 mm separately	1 - 27 psig / 1.5 bar 2 - 34 psig / 2 bar 3 - 34 psig / 2 bar 4 - 20 psig / 1.5 bar
*Note: Other outlet connections are available			

D50711	12	0050	05
BASIC SERIES	GAS	CONTROLLED PRESSURE RANGE	OUTLET PORT CONNECTION
D50711 Doppelregulus	02 - Nitrogen 08 - Air 09 - Synthetic air 12 - Oxygen 13 - Nitrogen oxide 15 - CO ₂ and inert gases 16 - Flammable gases (except Propane and Acetylene) 17 - Calibration gases 42 - Compressed air (370 psig / 300 bar)	0050 - 0.27 psig / 0.02 bar 0100 - 1.45 psig / 0.10 bar 0500 - 7.25 psig / 0.50 bar 1000 - 14.5 psig / 1.00 bar 1500 - 27 psig / 1.5 bar	05 - Compression fitting 6 mm with hose nipple 6 mm separately
*Note: Other outlet connections are available			



All dimensions are reference & nominal
 Metric [indicated] equivalents are in brackets

