

OHJAUSKOTELO CC-3000

CC-3000 OHJAUSKOTELO

Kustomoitava kotelo

- Valmistetaan mittojen mukaan
- Kotelon runkona alumiiniprofiili
- Tyylikäs teollinen ulkonäkö
- RAL9006
- Kotelointiluokka IP65



TUOTEKUVAUS

Bernsteinin kotelon runko on alumiiniprofiilia, joka tehtaalla kasataan kulmapaloilla kehikoksi. Etu- ja takalevy voidaan asentaa avattavaksi tai kiinteäksi tarpeen mukaan. Kotelon pituus ja leveys on valittavissa, käytettävä syvyys on enimmillään 246 mm. Kotelo voidaan toimittaa kahvoilla tai ilman. Näppäimistöille löytyy tarvittaessa myös asianmukainen teline. Kysy myös muista ohjeuskotelo vaihtoehdoista Kone-osastoltamme.

TEKNISET TIEDOT

SUOJAUS JA HYVÄKSYNNÄT

IP-luokka	IP65
Min. käyttölämpötila	-30 °C
Max. käyttölämpötila	80 °C
Väri	Harmaa
Materiaali	Alumiini





Single section configuration			
Front panel	Rear panel	Section depth	Installation depth
A Internally mounted	Fixed or hinged	120	103
		200	183
B Externally mounted	Fixed or hinged	120	111
		200	191



Aluminium section depth comparison
200 mm (left) and 120 mm (right)

Single section configuration			
Front panel	Rear panel	Section depth	Installation depth
A Internally mounted	Fixed or hinged	120	103
		200	183
B Externally mounted	Fixed or hinged	120	111
		200	191



Aluminium section depth comparison
200 mm (left) and 120 mm (right)

Configuration with combination of two sections (as door)			
Front panel	Rear panel	Section depth	Installation depth
C Internally mounted	Internally mounted	120+55	149
		200+55	229
D Externally mounted	Internally mounted	120+55	157
		200+55	237
E Internally mounted	Externally mounted	120+55	157
		200+55	237
F Externally mounted	Externally mounted	120+55	166
		200+55	246



120 mm section with additional
door extension (55 mm)

Configuration with combination of two sections (as door)			
Front panel	Rear panel	Section depth	Installation depth
C Internally mounted	Internally mounted	120+55	149
		200+55	229
D Externally mounted	Internally mounted	120+55	157
		200+55	237
E Internally mounted	Externally mounted	120+55	157
		200+55	237
F Externally mounted	Externally mounted	120+55	166
		200+55	246



120 mm section with additional
door extension (55 mm)