

JALKAKYTKIN

606.1600.002

Jalkakytin F1-U1YUN, 1-poljin, push-push, 1 NO+1
NC, suoja (2363507)

- Tukeva rakenne
- Kotelointiluokka IP65
- Rele, kontaktori ym. voidaan asentaa suojan sisään
- Saatavana myös erikoismalleja esim. sairaalakäyttöön



TUOTEKUVAUS

Koodien selitykset:

F1 = 1 poljin

F2 = 2 poljinta

UN = Varvasuoja

U1Z = Hidaskosketin, 1 NO+1 NC

Mechanical data	
Enclosure	Cast aluminium (powder coated)
Cover, Protective shroud UN	Cast aluminium (powder coated)
Foot pedal	Thermoplastic
Operating temperature (with no icing / no condensation)	-30°C to +60°C / -20°C to +60°C in type designation "EX")
Storage temperature	-30°C to +60°C / -20°C to +60°C in type designation "EX")
Mechanical service life	> 1 x 10 ⁷ switching cycles when using switches with potentiometer 1 x 10 ⁷
Switching frequency	10 min ⁻¹ when using switches with potentiometer 10 min ⁻¹
Type of connection	Screw connections (M20)
Conductor cross section	Single wire 0.5 – 1.5 mm ² or stranded wire with fibre 0.5 – 1.5 mm ²
Cable entry	M20 x 1.5
Weight with cover	F1 = 0.8 kg, F2 = 1.7 kg, F3 = 3.0 kg
Weight with protective shroud UN	F1 = 1.3 kg, F2 = 2.6 kg, F3 = 5.4 kg
Protection class	Protection class depends on type. Standard is IP 65.