OEM Finland Oy | Puh: 0207 499 499 | info@oem.fi | www.oem.fi
PL 9, 20101 TURKU

# JALKAKYTKIN

606.1300.011
Jalkakytkin F1-SU1Z, 1-poljin, 1 NO+1 NC, momenttikosketin

- Tukeva rakenne
- Kotelointiluokka IP65
- Rele, kontaktori ym. voidaan asentaa suojan sisään
- Saatavana myös erikoismalleja esim. sairaalakäyttöön

## TUOTEKUVAUS

| Koodien selitykset: | |
|---|---|
| **F1 =** | 1 poljin |
| **F2 =** | 2 poljinta |
| **UN =** | Varvassuoja |
| **U1Z =** | Hidaskosketin, 1 NO+1 NC |

| | |
|---|---|
| **U2Z =** | Hidaskosketin, 2 NO+2 NC |
| **SU1Z =** | Momenttikosketin, 1 NO+1 NC (kosketin vaihtaa tilaansa vakionopeudella, ”naksahtava”) |
| **SU2Z =** | Momenttikosketin, 2 NO+2 NC (kosketin vaihtaa tilaansa vakionopeudella, ”naksahtava”) |
| **U1Y =** | ”Push-push” –kosketin. Kerran painettaessa koskettimet vaihtavat tilaansa, ja toisen kerran painettaessa palautuvat alkutilaansa, 1 NO+1 NC. |
| **U2ZD =** | Kaksoistoiminta: ensimmäinen kosketinpari toimii painettaessa poljinta vasteeseen asti, toinen pari kytkeytyy mukaan kun poljinvoimaa lisätään ja painetaan pohjaan asti, 2 NO+2 NC. |

# TEKNISET TIEDOT

## TIEDOT

| | |
|---|---|
| **Koskettimet** | 1 NO, 1 NC |
| **IP-luokka** | IP65 |
| **Max. jännite** | 240 V |
| **Nimellisvirta, terminen** | 10 A |
| **Kaapelisisäänmeno** | 3xM20x1,5 |
| **Rungon materiaali** | Alumiini |
| **Polkimien määrä** | 1 |
| **Polkimen materiaali** | Muovi |
| **Min. käyttölämpötila** | -30 °C |
| **Max. käyttölämpötila** | 80 °C |
| **Max. toimintataajuus** | 50 kertaa/min |
| **B10d** | 20x10^6 |
| **Hyväksynnät** | CCC, CE, CSA US |






Standard values for safety technology

B10d 20 x 10^6
6 x 10^6 Restrictions in article designation "C" *
2 x 10^6 Restrictions in article designation "D" *
4 x 10^6 Restrictions in article designation "EX" *
1 x 10^6 Restrictions in article designation "ZS" *
* Once a restriction exists, the lowest value needs to be applied.

This technical data is generic to our standard foot switch range, please refer to individual technical data sheets for exact product information as the technical data above may vary.


Standards

VDE 0660 T100, DIN EN 60947-1, IEC 60947-1
VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1

Approvals*

CCSAUS A300, Q300 (same polarity)
cULus B300 (in type designation "ZS")
DGUV (Only switches that have an appropriate label.)
* Approvals depend on type.
More information can be found in the data sheet.

| Mechanical data | |
|---|---|
| **Enclosure** | Cast aluminium (powder-coated) |
| **Cover, Protective shroud UN** | Cast aluminium (powder-coated) |
| **Foot pedal** | Thermoplastic |
| **Operating temperature** (with no icing / no condensation) | -30°C to +80°C (-20°C to +65°C in type designation "EX") |
| **Storage temperature** | -30°C bis +80°C (-20°C to +65°C in type designation "EX") |
| **Mechanical service life** | > 1 x $10^6$ switching cycles when using switches with potentiometer 5 x $10^5$ |
| **Switching frequency** | 50 $min^{-1}$ when using switches with potentiometer 20 $min^{-1}$ |
| **Type of connection** | Screw connections (M3,5) |
| **Conductor cross sections** | Single-wire 0,5 – 1,5 $mm^2$ or stranded wire with ferrule 0,5 – 1,5 $mm^2$ |
| **Cable entry** | M20 x 1,5 |
| **Weight with cover** | F1 = 0,6 kg, F2 = 1,7 kg, F3 = 3,0 kg |
| **Weight with protective shroud UN** | F1 = 1,5 kg, F2 = 2,6 kg, F3 = 5,4 kg |
| **Protection class** | Protection class depends on type. Standard is IP 65 |