

## JALKAKYTKIN

606.1800.012

Jalkakytin F1-SU1ZUN, 1-poljin, 1 NO+1 NC,  
momenttikosketin, suoja

- Tukeva rakenne
- Kotelointiluokka IP65
- Rele, kontaktori ym. voidaan asentaa suojan sisään
- Saatavana myös erikoismalleja esim. sairaalakäyttöön



## TUOTEKUVAUS

---

### Koodien selitykset:

---

**F1 =** 1 poljin

---

**F2 =** 2 poljinta

---

**UN =** Varvassuoja

---

**U1Z =** Hidaskosketin, 1 NO+1 NC

---



| Mechanical data                                         |                                                                                                   |
|---------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Enclosure                                               | Cast aluminium (powder coated)                                                                    |
| Cover, Protective shroud (N)                            | Cast aluminium (powder coated)                                                                    |
| Foot pedal                                              | Thermoplastic                                                                                     |
| Operating temperature (with no icing / no condensation) | -30°C to +60°C / -20°C to +60°C in type designation "EX")                                         |
| Storage temperature                                     | -30°C to +60°C / -20°C to +60°C in type designation "EX")                                         |
| Mechanical service life                                 | > 1 x 10 <sup>7</sup> switching cycles when using switches with potentiometer 1 x 10 <sup>7</sup> |
| Switching frequency                                     | 10 min <sup>-1</sup> when using switches with potentiometer 10 min <sup>-1</sup>                  |
| Type of connection                                      | Screw connections (M20)                                                                           |
| Conductor cross section                                 | Single wire 0.5 – 1.5 mm <sup>2</sup> or stranded wire with bundle 0.5 – 1.5 mm <sup>2</sup>      |
| Cable entry                                             | M20 x 1.5                                                                                         |
| Weight with cover                                       | F1 = 0.8 kg, F2 = 1.7 kg, F3 = 3.0 kg                                                             |
| Weight with protective shroud (N)                       | F1 = 1.3 kg, F2 = 2.6 kg, F3 = 5.4 kg                                                             |
| Protection class                                        | Protection class depends on type. Standard is IP 65.                                              |