

TERMOELEMENTTI ILMAN SUOJATASKUA

TC10-H

TC10H-14341557

K Tyyppi 0-1260°C 250x6mm BSZ Ilman johtoa



- Mitta-alue -40-1260°C
- Tyyppi K, J, E, N tai T
- Yksi- tai kaksi johdinta
- 4-20mA+Hart optio
- Atex optio

TUOTEKUVAUS

Termoelementit ilman suojataskua soveltuvat erityisesti käyttökohteisiin, joissa anturin metallikärki asennetaan suoraan porattuun reikään (esim. koneen osaan) tai suoraan prosessilinjaan, jossa ei käytetä kemiallisesti aggressiivisia tai hankaavia aineita.

Vaihtoehtoisesti liitäntäpäähän voidaan liittää WIKAN tuotevalikoiman analogisia tai digitaalisia lähettämiä.

TEKNISET TIEDOT

Aineen kanssa kosketuksissa olevien osien materiaali	Ruostumaton teräs 316Ti
Asennussyvyys	250 mm
IP-luokka	IP65
Kytinkotelon materiaali	Ruostumaton teräs 316Ti
Max. käyttölämpötila	1260 °C
Max. ympäristön lämpötila	80 °C
Min. käyttölämpötila	0 °C
Min. ympäristön lämpötila	-40 °C
Pistokkeen halkaisija	6 mm
Rungon materiaali	Alumiini

Connection head



Model	Material	Cable entry thread size	Ingress protection (max.)	Cap	Surface	Connection to rock tube
JS	Aluminium	M16 x 1.5	IP65	Cover with 2 screws	Blue, lacquered	M24 x 1.5, 1/4 NPT
BS	Aluminium	M20 x 1.5 or 1/4 NPT	IP65, IP68	Flat cap with 2 screws	Blue, lacquered	M24 x 1.5, 1/4 NPT
BSZ	Aluminium	M20 x 1.5 or 1/4 NPT	IP65, IP68	Spherical hinged cover with cylinder head screw	Blue, lacquered	M24 x 1.5, 1/4 NPT
BSZ-H	Aluminium	M20 x 1.5 or 1/4 NPT	IP65, IP68	Raised hinged cover with cylinder head screw	Blue, lacquered	M24 x 1.5, 1/4 NPT
BSZ-H (ex cable outlet)	Aluminium	2 x M20 x 1.5 or 2 x 1/4 NPT	IP65, IP68	Raised hinged cover with cylinder head screw	Blue, lacquered	M24 x 1.5, 1/4 NPT
BSZ-H / DH10	Aluminium	M20 x 1.5 or 1/4 NPT	IP65	Raised hinged cover with cylinder head screw	Blue, lacquered	M24 x 1.5, 1/4 NPT
BS5	Aluminium	M20 x 1.5 or 1/4 NPT	IP65	Spherical hinged cover with clamping lever	Blue, lacquered	M24 x 1.5, 1/4 NPT
BS5-H	Aluminium	M20 x 1.5 or 1/4 NPT	IP65	Raised hinged cover with clamping lever	Blue, lacquered	M24 x 1.5, 1/4 NPT
BVS	Stainless steel	M20 x 1.5	IP65	Precision-cast screw-on lid	Blank, electropolished	M24 x 1.5
BSZ-K	Plastic	M20 x 1.5 or 1/4 NPT	IP65	Spherical hinged cover with cylinder head screw	Black	M24 x 1.5
BSZ-HK	Plastic	M20 x 1.5 or 1/4 NPT	IP65	Raised hinged cover with cylinder head screw	Black	M24 x 1.5

Model	Explosion protection				
	without	Ex I (gas) Zone 0, 1, 2	Ex I (dust) Zone 20, 21, 22	Ex II A (gas) Zone 2	Ex II (dust) Zone 22
JS	x	x	-	-	-
BS	x	x	-	-	-
BSZ	x	x	x	x	x
BSZ-H	x	x	x	x	x
BSZ-H (ex cable outlet)	x	x	x	x	x
BSZ-H / DH10	x	x	-	-	-
BS5	x	x	-	-	-
BS5-H	x	x	-	-	-
BVS	x	x	-	-	-
BSZ-K	x	x	-	-	-
BSZ-HK	x	x	-	-	-

Electrical connection



For the electrical connections of built-in temperature transmitters see the corresponding data sheets or operating instructions.

