OEM Finland Oy | Puh: 0207 499 499 | info@oem.fi | www.oem.fi
PL 9, 20101 TURKU

TAIPUISA MONIPISTEINEN LÄMPÖTILAMITTARI FLEX-O

TC96-O

TC96-O
Joustava putkiston lämpötilan monipistemittaus

- Jopa 10 mittauspistettä
- Erittäin joustava asennus
- Helppo puhdistaa
- Pituus aina 40m asti
- Saatavana vastusanturina

TUOTEKUVAUS

Lämpötilan monipistemittausta käytetään usein mittaamaan reaktorin lämpötilaprofiilia tai säiliön lämpötilaa tai kuumien pisteiden "hotspot" löytämiseksi. Jotta saavutetaan nopea vasteaika, on mittauselementti painettu jousivoimalla kiinni suojakuoren pintaan, jolloin mittapää ja suojakuori muodostaa yhden kokonaisuuden.
Liittimet ja lämpötilalähettimet asennetaan kytkentäkoteloon, joka on liitettynä monipistemittaukseen tai ne voidaan asentaa erillisenä keskuskoteloon.

TEKNISET TIEDOT

Aineen kanssa kosketuksissa olevien osien materiaali	Alloy, Hiiliteräs
Materiaali	Ruostumaton teräs 316L, Ruostumaton teräs 316Ti







Pipe dimensions Ø F_1
- 1 1/4 NPS
- 1 1/2 NPS
- 2 NPS
- 3 NPS

Other sizes available

Insertion length U
Freely selectable (max. 40 m)

Material
- Stainless steel 316
- Stainless steel 316L

Other materials available

■ Process connection



Seal clamp connector



Seal flange



Seal plate



Support plate



Connection terminal



Transmitter



Transmitter on terminal



Terminal on transmitter on terminal



Case, remote attachment with conduit



Case, direct attachment